



**POWERCAP INSTALLATION:**

\* - REFERENCE USER MANUAL FOR POWERCAP REMOVAL AND BATTERY REPLACEMENT

1. AFTER REMOVING POWERCAP AND O-RINGS, WIPE O-RINGS AND POWERCAP WITH A CLEAN, DRY TOWEL, ENSURING NO DIRT OR OTHER CONTAMINANTS.
2. APPLY A LIGHT COATING OF O-RING LUBE TO THE O-RINGS. NOTE: MAKE SURE GREASE DOES NOT GET INTO ANY ELECTRICAL CONNECTIONS, AS THIS MAY CAUSE DAMAGE TO THE HUB OR POWERCAP.
3. INSTALL QUAD RING ONTO TORQUE TUBE, ENSURING IT IS NOT TWISTED AND PROPERLY SEATED IN GROOVE.
4. SEAT THE RED POWERCAP O-RING INTO THE NON-DRIVE SIDE OF THE HUB.
5. INSTALL THE POWERCAP AND TIGHTEN THREADED NUT HAND TIGHT TO SECURE.

**GREASING / REPLACING FREEHUB BODY**

\* - HEAVY USE OR WET RIDING CONDITIONS MAY CAUSE GREASE TO MIGRATE OUT OF HUB.

\* - O-RING LUBE: SILICONE BASED O-RING LUBRICANT  
DOW CORNING III VALVE LUBE & SEALANT.

1. PULL DRIVE SIDE END CAP OFF OF AXLE USING AN AXLE VISE. SLIDE FREEHUB OFF THE AXLE.
2. WIPE ALL SURFACES AND RATCHET RINGS CLEAN TO ENSURE NO CONTAMINATION.
3. APPLY A 0.75mL AMOUNT OF GREASE ON THE RATCHET RING.
4. TO REASSEMBLE, SLIDE THE FREEHUB ONTO THE AXLE. SPIN/ORIENT THE FREEHUB TO ALLOW PAWLS TO ENGAGE INTO THE RATCHET RING OF THE HUB. PRESS ENDCAP ONTO AXLE AND MAKE SURE IT IS FULLY SEATED.

		<p><b>SARIS CYCLING GROUP</b> 5253 VERONA RD., MADISON WI. 53711 1-800-783-7257 / 1-608-274-6550 WWW.SARIS.COM WWW.CYCLEOPS.COM WWW.POWERTAP.COM</p>
		<p>© SARIS CYCLING GROUP 2014 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE CONFIDENTIAL PROPERTY OF SARIS CYCLING GROUP ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SARIS CYCLING GROUP IS PROHIBITED.</p> <p>TITLE: <b>24614 - G3 DISK HUB</b></p>